



DUCHESNE COUNTY MONUMENT SURVEY RECORD

T1S R1W

SEC 19 | SEC 20
SEC 30 | SEC 29

U.S.B.&M.


J-5



SCALE: 1"=30'



5/8"X24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT 1/4 CORNER



SET 5/8"X24" REBAR
WITH ORANGE CAP
STAMPED PLS 1489512
AS REFERENCE POINT

SET 5/8"X24" REBAR
WITH ORANGE CAP
STAMPED PLS 1489512
AS REFERENCE POINT

NOTE:
THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED
FROM G.P.S. OBSERVATIONS AT A CONTROL POINT
(SECTION CORNER) LOCATED AT LAT. 40°23'20.57790"N
AND LONG. 110°01'46.98583"W USING THE UTAH STATE
G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK
MAINTAINED AND OPERATED BY THE AUTOMATED
GEOGRAPHIC REFERENCE CENTER

SURVEY MARKER AND
WASHER AT 1/16 CORNER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A REBAR WITH AN ALUMINUM
CAP AT THE POSITION OF THE
SECTION CORNER



DESCRIPTION OF MONUMENT AND ACCESSORIES
ESTABLISHED TO PERPETUATE THE ORIGINAL
LOCATION OF THE CORNER

SET A 5/8"X24" REBAR WITH A 2 1/2"
ALUMINUM DUCHESNE COUNTY
MONUMENT AT THE POSITION OF THE
SECTION CORNER

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
NAD83 UTAH CENTRAL ZONE
N: 7308541.422
E: 2050045.116
NAVD88 EL: 5605.298'

LATITUDE: 40°22'28.51872" N
LONGITUDE: 110°01'46.83975" W
ELLIPSOID HEIGHT: 5550.16'
(GEOID 03 CONUS)
PUBLIC LAND SURVEY SYSTEM GCDB ID NO.
UT300010S0010W0_200300

CERTIFICATION

I Jerry D. Allred, Professional Land Surveyor, State of Utah, do
hereby certify that I have performed or reviewed the work done on the
diagrammed corner as reported on this recordation form and approve same

Date 28 FEB 2018

Jerry D. Allred, Professional Land Surveyor
Certificate No. 148951
Duchesne County Surveyor

